

AstroPure Commercial Air Purifiers



AstroPure - High purity filtration solutions for areas where additional, extra high, filtration performance is needed.

AstroPure

Air purification system

Product description

AstroPure is a totally self-contained stand-alone Recirculation Unit for areas where additional, extra high, filtration performance is needed against any type of contamination including viruses.

AstroPure, which can also be used as a Negative Pressure Unit, combines state-of-the-art HEPA filtration with optionally available UV germicidal irradiation (UVGI) to create total clean air solutions fulfilling all relevant guidelines such as the VDI 6022. Thanks to the insulated double-wall constructions leading to whisper-quiet operation, it is ideally suitable for indoor use in for example offices, schools, health care facilities or hotel lobbies, just to name a few. When properly sheltered outdoor use with duct connection is also possible.

Together with the ability to take various filter combinations and variance of optional features, AstroPure provides herewith highest flexibility to meet all customer-specific requirements at point of use.

The unit contains a high performance encapsulated AAF optimized direct driven backward curved EC fan/motor combination with variable speed and control options with CE compliance.

Plug & Play Design

To allow economical and easy installation AstroPure is designed as a Plug & Play unit hence no modifications required at your premises. Simply install the selected air filters and dispose it when no longer effective.

Maintaining the unit is as easy as the installation itself. The sliding tray design provides easy access to and servicing of the fan. The easy to access instrument panel provides easy access and servicing of gauges and speed control.

Features & Benefits

- › Suitable for in-room use or sheltered outdoor installation
- › Airflow rate up to 2,000 m³/h
- › HEPA H14 filter in accordance with EN1822
- › Pre-filter options up to ISO Coarse 70%
- › Optional UV germicidal irradiation (UVGI)
- › Insulated double-wall construction provides whisper-quiet operation down to 35 dB(A)
- › Designed with internal variable speed fan (electronically commutated) and filter combinations to meet specific application requirements
- › Easy installation, operation, and maintenance in a totally self-contained system
- › Sliding tray design provides easy access and servicing of filters
- › CE-compliance, VDI 6022 guided design



Applications



Schools and Universities



Commercial Buildings



Healthcare



Hospitality



Shops and Shopping malls



Models

Model	BR00000554	BR00000749	BR00000676	BR00000751	BR00000678	BR00000752
Plug type	EU	UK	EU	UK	EU	UK
HEPA Filter (H14)		✓		✓		✓
LCD Screen				✓		✓
Activ. Carbon (Gas phase) pre-filter				✓		✓
UV light						✓

Technical data

	BR00000554	BR00000749	BR00000676	BR00000751	BR00000678	BR00000752
Design air flow rate	m ³ /h		2,000			
Application	Floor standing type					
Casing	Colour		Painted galvanized steel finish			
Dimensions	Unit	HxWxD	mm			
Weight	Unit		kg			
Pre-filter	Dust collecting method		Prefilter RedPleat, ISO Coarse 70%	Prefilter RedPleat Carb, ISO Coarse 65% gas phase filter		
HEPA filter	Bacteria filtering method		Astrocel III HEPA H14			
Air purifying operation	Power input	High fan speed	kW			
UV-irradiation unit	Power input		kW			
Sound pressure level	Air purifying operation	High fan speed	dBA			
Fan Motor	Stepless adjustable					
Safety devices	Item		Safety switch (operation stops when the back door is open)			
Standard Accessories	Prefilter		1			
	HEPA filter		1			
	Quick Start and Maintenance Guide		1			
	Installation and Operation Manual		1 (download)			
Power cord	m		3			
Power supply	Phase		1~			
	Frequency		Hz			
	Voltage		V			
Running current	Air purifying operation	High fan speed	A			

Highly Adaptable

Available as recirculation or negative pressure unit

Clean Air supply options

AstroPure is used to draw out the indoor contaminated air in a room, the contaminated air passes the HEPA filter before releasing it to the outside environment.


Negative pressure from a room prevents the spread of virus to other rooms, areas and environment. Highly recommended to improve IAQ by recirculating indoor air and providing occupants with better health and comfort.



- A** Fan / Motor Unit
- B** HEPA Filter
- C** Prefilter
- D** Control panel providing indication for filter change, speed control and on/off switch
- E** Air outlet grill
- F** UV lamp
- G** 4-Wheel foundation

Unit control options

On the front side AstroPure is as a standard equipped with control lights to indicate necessary changes of the pre- or the HEPA filter. Switching the unit on and off as well as the speed control is done via integrated knobs. As an option AstroPure can be delivered with a fully digital LCD Display, which then replaces indicator lights and control knobs.



Fan/motor combination

AstroPure contains a high performance encapsulated, direct driven, backward curved fan/ motor combination. Motor options are available to create air flows up to 2000 m³/h. The specialized electronic commutation motor design permits variable speed control via Potentiometer. The complete section is mounted on a sliding tray providing easy access to service the fan.



Standard Configurations

Construction	Insulated double-wall construction
Power supply	Single-phase 200-277 VAC, 50/60 Hz
Recommended operational airflow	2.000
Fan type	EC centrifugal fan, backward-curved, single-intake
Prefilter	RedPleat, ISO coarse 70%, card board frame (ISO16890)
Main filter	AstroCel III H14 HEPA filter, metal frame (EN1822)
Air inlet	Inlet grilles or inlet duct
Air outlet	Outlet grilles or outlet duct (circular / rectangular)
Deployment	4x castor rolls for easy maneuverability
Allowed operating conditions	0 – 50° C, H0 dry environment, ambient air ≤ 95% rH

Note: Definite recommendation on prefilter and main filter needs to be done case by case depending on local conditions.

Prefilter options

In its standard configuration AstroPure is equipped with an RedPleat ISO coarse 70% prefilter. As an option the unit can also be equipped with RedPleat Carb, an ISO coarse 65% Prefilter including active carbon media able to additionally control unpleasant odors in the room.



Air supply options

When operated as a Recirculation Unit, AstroPure releases the cleaned air via a perforated outlet grill on the top side of the unit into the room. Optionally, the air outlet can be designed so that the AstroPure unit can be connected to ventilation ducts.




Easy filter installation and maintenance

The unique design of the clamping system is designed to take various AAF pre and main filters and hereby ensures easy installations and filter maintenance and dispose when no longer effective. The complete servicing is done from the back-side.



Optional UV lamp

Intelligently engineered to kill pathogens while maintaining higher filtration performance. The optional available fluorescent UV-C irradiation unit radiates 255 nm germicidal wavelength which prevents the Ozon production that is responsible for faster degradation of filters while keeping the appropriate range to kill bacteria and viruses. Installing UV lamp will provide wider germicidal coverage without affecting the filtration efficiency.



Providing high-efficiency 2-stage filtration

Prefilters

The Standard installation includes an ISO Coarse 70% pre-filter providing the lowest possible total cost of ownership with lower resistance, longer filter life and protection of the installed HEPA filter.

RedPleat - 4531002424

- › ISO 16890: ISO coarse 70%
- › Low pressure drop
- › High dustholding capacity (DHC)
- › Available with Antimicrobial treated media (RedPleat ULTRA)



RedPleat Carb - 4139002424

- › ISO 16890: ISO coarse 65%
- › Low pressure drop
- › High dustholding capacity (DHC)
- › Effectively removes offensive odors




Main filter

The HEPA filter features eFRM filtration media which combines ultra-high efficiency and particulate loading to remove 99.99% of dust, pollen, mold, bacteria, viruses, and any airborne particle with a size of 0.3 microns or greater.

AstroCel® III - 1493299990

- › H14 filtration efficiency according EN 1822
- › V-shaped filter configuration, combined with microglass media, delivers higher flow and the lowest possible pressure drop vs traditional box style HEPA filters
- › Utilizes high performance microglass media to provide high efficiency particulate removal
- › Compatible with Discrete Particle Counter (DPC) and photometric test methods as access and instrumentation allow





RedPleat Carb



AstroCel® III



Daikin Air Purification Solutions

For your home & for your business

Improve your Indoor Air Quality with air purifying technology from Daikin. For clean and healthy air no matter where you are.

Daikin streamer technology air purifier (MC55W) & Humidifying streamer technology air purifier (MCK55W)

- › Pure air thanks to active plasma ion flow out and flash streamer technology
- › High performance HEPA filter to catch fine particles of dust
- › Humidification and purification in one (MCK55W only)
- › Powerful suction and whisper quiet
- › New stylish and compact design

AAF AstroPure 2000

- › Self-contained stand-alone recirculation unit (1628mm height)
- › Standard high efficiency HEPA H14 filters
- › Optional UV germicidal irradiation
- › Plug & Play
- › Air flow rate 2000 m³/h
- › For commercial areas up to 200 m²



Clean the air from

Viruses and bacteria


Fine particles of dust

Odors and allergens

https://www.daikin.eu/en_us/about/daikin-innovations/indoor-air-quality.html



Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Publisher)



ECPEN21-705A

08/21



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.