



Ururu streamer  
technology air  
purifier  
MCK 70ZW/ZH



Humidification



Flash Streamer



Onecta via app

Humidification and air purification in one

- > Onecta app
- > Air purification for large spaces up to 96 m<sup>2</sup>
- > Daikin's Catch and Clean approach
- > Intuitive display design

- > Whisper quiet
- > High performance electrostatic HEPA filter
- > Filter lifetime of ten years

# MCK70ZW/MCK70ZH



MCK70ZW/ZH

Indoor Unit		MCK	70ZW/ 70ZH
Application			Floor standing type
Applicable room area		m <sup>2</sup>	48 (1) / 96 (2)
CADR		m <sup>3</sup> /h	375 (3)
Weight	Unit	kg	12.5
Dimensions	Unit	Height x Width x Depth	mm
Casing		Colour	White/Black
Fan	Type		Multi Blade Fan (Sirocco fan)
Airflow rate	Air purifying operation	Silent/Low/Medium/Turbo	m <sup>3</sup> /h
	Humidifying operation	Silent/Low/Medium/Turbo	m <sup>3</sup> /h
Sound pressure level (5)	Air purifying operation	Silent/Low/Medium/Turbo	dBA
	Humidifying operation	Silent/Low/Medium/Turbo	dBA
Humidifying operation	Power input	Silent/L/M/Turbo	kW
	Humidification	Turbo	ml/h
	Water tank capacity		l
Air purifying operation	Power input	Silent/L/M/Turbo	kW
Deodorizing method	Flash streamer + Deodorizing catalyst		
Dust collecting method	Electrostatic HEPA filter (7)		
Air filter	Type	Polyethylene terephthalate net	
Sign	Item	01	Humidity monitor lamp: 5 stages / PM 2.5 sensor lamp: 3 stages / Odour sensor lamp: 3 stages / Humidity setting: Low/Standard/High / AUTO FAN mode / Econo mode / Anti-pollen mode / MOIST mode / CIRCULATION mode / Child proof lock lamp / Water supply lamp / AUTO operation lamp / Streamer lamp / AIR MONITOR indicator: 0µg/m <sup>3</sup> - 99µg (8) / m <sup>3</sup> / 0°C - 39°C, 20% - 90% / FAN lamps: Quiet/Low/Standard/Turbo / Humidifier ON/OFF lamp / Daikin eye / AIR MONITOR setting lamps / Communication lamp
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220-230
Type	Humidifying air purifier		

(1) The coverage area is appropriate for operating the unit of maximum fan speed(HH).Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. |

(2) Converted to NRCC standards from test values in accordance with JEM1467. |

(3) Converted to CADR standards from test values in accordance with JEM1467. |

(4) Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. |


(5) Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) |

(6) Electrostatic HEPA filter and humidifying filters are attached in the unit. |

(7) Requirements according to JEM1467. |

(8) "HI" is displayed when the PM2.5 concentration exceeds 99µg/m<sup>3</sup>.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



ECPEN23-619



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.